2 Series MSO vs. Rigol DHO4000

COMPETITIVE FACT SHEET

Visualization & Usability

Tektronix 2 Series MSO

- 10.1-inch WXGA (1280 x 800) resolution display with touchscreen
- Touchscreen capabilities with intuitive control commands
- Ability to view multiple waveform slices in stacked mode
- Common user interface across the scope family



Rigol DHO4000

- 10.1-inch WVGA 1280 X 800 resolution display with touchscreen
- ✓ Touchscreen capabilities
- waveform view is limited to one display window
- Different user interfaces across different models



Portability & Physical Characteristics

Tektronix 2 Series MSO

- Battery: Optional battery pack can power the instrument for up to 8 hours
- Weight: 4 lbs standalone and 8 lbs

 ✓ total with battery pack and two
 batteries
- Footprint: 8.26" x 13.54" x 1.59" (H x ✓ W x D) dimensions allows for more desk space
- Flexibility: VESA Mount allows for the scope to be positioned in many ways

Rigol DHO4000

- ✓ Battery: Optional battery pack
- Weight: 8.4 lbs is heavier than the 2 Series MSO without the battery pack
- Footprint: "8.45" x 14.1" x 4.75" (H x W x D) dimensions takes up more space on the lab bench
- ✓ Flexibility: Support for VESA Mount

Key Specifications Comparison				
	Tektronix 2 Series MSO		Rigol DHO4000	
Analog Channels	✓	2, 4	✓	4
Digital Channels	✓	16 (with option 2-MSO)	x	No
Bandwidth	x	70, 100, 200, 350, 500 MHz	✓	200, 400, 800 MHz
Max. Sample Rate	✓	1.25 GS/s (all channels on) 2.5 GS/s (half channels on)	x	1 GS/s (per channel) 2 GS/s (half channels)
Max. Record Length (All channels on)	×	10 M points	✓	62.5 M points
Maximum Input Voltage	✓	CATII 300 Vrms	x	CATI 300 Vrms
Standard Trigger Types	×	Edge, Pulse Width, Runt, Timeout, Logic, Setup & Hold, Rise/Fall Time, Parallel Bus	✓	Edge, Pattern, Pulse Width, Video, Timeout, Runt, Window, Setup/Hold, Delay, Nth Edge, Serial Bus
Arbitrary Function Generator (AFG)	✓	1-channel, 50 MHz	x	No
Digital Pattern Generator	✓	4 channels, 4k memory length, up to 25 Mbps	×	No



2 Series MSO vs. Rigol DHO4000

COMPETITIVE FACT SHEET

Tektronix 2 Series MSO

- **Help:** Shows graphical images and explanatory text to provide quick feature overviews. Application notes and more information available on website
- Feature Control: Allows disabling of autoset, cursors, and automated measurements
- ✓ Front Panel: Simplified front panel with LED color coded ring lights
- **Highly Customizable Software:** Change font sizes, colors, autoset, window sizes, and much more
- PC Analysis: Perform advanced analysis using TekScope™, with same UI as 2 Series



Rigol DHO4000

- Built-in help menu provides help on selected options
- No feature control available
- √ Simplified front panel
- No customizability options
- No comprehensive software to perform advanced analysis on PC



Measurement

Tektronix 2 Series MSO

- Display unlimited measurements either as
- measurement badge or collectively in a results table
- One set of cursors per display, can be enabled in any window simultaneously
- Perform serial protocol triggering and analysis on the most common buses (requires 2-SERIAL)
- ✓ Unlimited math waveforms and reference signals
- ✓ Gate both measurements and FFTs
- × 37 automatic measurements
- Frequency Response Analysis (Bode plot, requires 2-SOURCE)

Rigol DHO4000

- Maximum of 14 active measurements at once
- Two set of XY cursors
- Serial triggering and decoding standard
- 4 math waveforms and 10 reference waveforms
- No measurement or FFT gating
- √ 41 automatic measurements
- No Bode plot

Connectivity

Tektronix 2 Series MSO

- ✓ Two USB 2.0 HOST ports
- ✓ One USB DEVICE port
- ✓ Ethernet port for network connectivity

TekDrive™ is natively integrated as a T&M

- collaborative data workspace that allows for seamless data access anywhere and much more
- No HDMI output port



Rigol DHO4000

- ✓ Two USB 3.0 HOST port
- ✓ One USB 3.0 DEVICE port
- ✓ Ethernet port

Web Control Interface allows waveform

- control, measurement and analysis. No data collaboration sharing.
- ✓ HDMI output port



