


# MDO4000C Series vs. Rohde & Schwarz FSV Spectrum Analyzer

## COMPETITIVE FACT SHEET



### Mixed Domain Oscilloscope

- 4 analog channels
- 16 digital channels (optional)
- Integrated spectrum analyzer
- ← ▪ Dedicated front panel controls
- ← ▪ Dedicated N connector
- Integrated arbitrary/function generator (optional)
- Serial bus decoding and triggering (optional)


Specifications		Tektronix MDO4000C w/ opt. SA3		Rohde & Schwarz FSV4
Frequency Range	✗	9 kHz - 3 GHz	✓	10 Hz - 4 GHz
Capture / Analysis Bandwidth	✓	3 GHz	✗	28 MHz (options to 160 MHz)
Phase Noise at 1 GHz CF 10 kHz offset	✓	<-108 dBc/Hz, <-111 dBc/Hz (typical)	✗	<-106 dBc/Hz, <-110 dBc/Hz (typical)
100 kHz offset	✓	<-110 dBc/Hz, <-113 dBc/Hz (typical)	✗	<-115 dBc/Hz, <-115 dBc/Hz (typical)
Displayed Average Noise Level (DANL) at 1 GHz	✗	<-147 dBm/Hz, <-149 dBm/Hz (typical)	✓	<-150 dBm/Hz, <-153 dBm/Hz (typical)
2nd Harmonic Distortion at 1 GHz (0 dB atten.)	✓	<-60 dBc, <-65 dBc (typical)	✗	<-55 dBc
3rd Order Intermodulation Distortion at 1 GHz	✓	<-62dBc, <-65 dBc (typical)	✗	<-56 dBc, <-62 dBc (typical)
Other Input Related Spurious Response	✗	<-60 dBc, <-65 dBc (typical) w/ exceptions to <-55 dBc, <-60 dBc (typ.)	✓	<-70 dBc
Residual Response	✗	<-85 dBm w/ exceptions at <-78 and <-73 dBm	✓	<-103 dBm
Display Size and Resolution	✓	10.4" XGA	✗	8.4" SVGA
Dimensions (HxWxD in inches)	✓	9.0 x 17.3 x 5.8	✗	7.8 x 16.2 x 16.4
Weight	✓	11 lbs.	✗	20.9 lbs.
Warranty	✓	3 years	✗	1 year

# MDO4000C Series vs. Rohde & Schwarz FSV Spectrum Analyzer


## COMPETITIVE FACT SHEET

### MDO4000C Capabilities Not Available on Rohde & Schwarz FSV


- 4 analog channels and 16 digital channels
- Function generator and DVM
- Serial / Parallel bus decode
- Capture bandwidth wide enough for modern RF signals
- Time-correlated views of analog, digital, serial / parallel buses and RF signals for complete system visibility. RF signals include:
  - Spectrum shown in Frequency Domain
  - Amplitude, Frequency, and Phase vs. Time traces shown in Time Domain




**Correlating RF to other system signals**  
 The most common application is making timing measurements from control logic (often serial or parallel bus commands) to when the RF output changes take effect.




**Exceptionally Wide Capture Bandwidth**  
 With 3 GHz of capture bandwidth and long RF acquisition times, the MDO is the ultimate product for debugging modern wideband, time varying RF signals.



Time Domain Only



Frequency Domain Only



Both Domains at Once