

OSCILLOSCOPE

SELECTION GUIDE



Tektronix®

OSCILLOSCOPE SELECTOR GUIDE

Tektronix offers oscilloscopes for many different applications and uses. To help you choose the right scope for your needs, the most common criteria for selecting a scope are listed below, along with helpful tips for determining your requirements.

1 Bandwidth

All oscilloscopes have a low-pass frequency response that rolls off at higher frequencies. Oscilloscope bandwidth is specified as being the frequency at which a sinusoidal input signal is attenuated to 70.7% of the signal's true amplitude – the -3 dB point. Your oscilloscope must have sufficient bandwidth to capture all relevant frequency components of your signal. If you regularly work with digital signals, it may be easier to consider bandwidth by comparing signal and oscilloscope rise time specifications. Use an oscilloscope with a rise time specification five times faster than your signal rise time to keep error below 2%.

Rule: Bandwidth > 5 x Highest Signal Frequency

2 Sample Rate

The faster an oscilloscope samples, the greater the resolution and detail of the displayed waveform, and the less likely that critical information or events will be lost. Tektronix recommends at least 5X oversampling to ensure signal details are captured and to avoid aliasing.

Rule: Sample Rate > 5 x (Highest Frequency Component)

3 Record Length

Record length is the number of samples the oscilloscope can digitize and store in a single acquisition. Since an oscilloscope can store only a limited number of samples, the waveform duration – or length of “time” captured – will be inversely proportional to the oscilloscope’s sample rate. A longer record length enables a longer time window to be captured with high resolution.

Rule: Captured Time = (Record Length) / (Sample Rate)

4 Digital Channels and Spectrum Analyzer Input

Today’s oscilloscopes offer more than just analog channels for system-level troubleshooting of complex designs.

- If you need to analyze a parallel bus or multiple serial buses, the Tektronix MSO Series of mixed signal oscilloscopes and MDO Series of mixed domain oscilloscopes offer 16 digital channels and up to 4 analog channels for analyzing multiple signals at once.
- If you are working with RF signals, the Tektronix MDO Series of mixed domain oscilloscopes offers a built-in spectrum analyzer for time-correlated analysis of analog, digital and RF signals.

CONTENTS

CHOOSING YOUR OSCILLOSCOPE	1-3
MIXED SIGNAL AND MIXED DOMAIN OSCILLOSCOPES	
MSO/DPO2000B	4
MDO3000	4
MDO4000C	5
ADVANCED SIGNAL ANALYSIS OSCILLOSCOPES	
5 Series MSO	6
6 Series MSO	6
MSO/DPO5000B	7
DPO7000C Series	7
MSO/DPO70000 Series	8
DPO70000SX Series	8
BASIC OSCILLOSCOPES	
TBS1000	9
TBS1000B/TBS1000B-EDU	9
TBS2000	9
LOW PROFILE OSCILLOSCOPES	
5 Series MSO Low Profile	10
SAMPLING OSCILLOSCOPES	
DSA8300	10
BATTERY POWERED OSCILLOSCOPES WITH ISOLATED CHANNELS	
THS3000	11
TPS2000B	11
TDS SERIES OSCILLOSCOPES	
TDS2000C	11
TDS3000C	11
PROBES AND ACCESSORIES	
SERIAL SUPPORT SELECTOR BY MSO/DPO AND MDO PRODUCT SERIES	
	12-13
	14-17


5 Features and Analysis Capability

Tektronix oscilloscopes offer a range of features and analysis capabilities. When choosing your scope, you should review available triggers, waveform search tools, automated measurements, and analysis packages such as serial bus analysis, jitter and power analysis to ensure they meet your needs.

CHOOSING YOUR OSCILLOSCOPE

Engineers, technicians and educators all have different workloads, different measurement needs, and different environments. To meet your needs Tektronix offers a wide range of oscilloscopes. This guide gives an overview of the various types of oscilloscopes currently available, along with high-level specifications that you can use for comparison.

If you need a refresher on oscilloscope specifications, download the XYZs of Oscilloscopes Primer.



TYPES OF OSCILLOSCOPES



Mixed Domain Oscilloscopes – 100 MHz to 1 GHz

The new standard for design and debug work. They offer the same capabilities as mixed signal oscilloscopes, but also offer a built-in spectrum analyzer, adding RF debugging to the analog/digital capabilities.



Mixed Signal Oscilloscopes – 70 MHz to 8 GHz

The engineer's choice for design and debug. They combine traditional oscilloscope input channels with digital input channels, long record length with powerful search features, and protocol support for serial buses.


Advanced Signal Analysis Oscilloscopes – 350 MHz to 70 GHz

The emphasis is on analysis. They provide high acquisition performance and run Windows, thus supporting a wide range of analysis software. MSO versions include digital channels. They can be equipped for serial data analysis, jitter analysis, standards testing, and serial decoding capability.



Low Profile Oscilloscopes

When performance, channel density and cost-per-channel are critical, these low-profile instruments are a great fit. They offer the same performance as bench instruments in a rack-friendly form factor.




VOTED 2017
INDUSTRY BEST -
[LEARN MORE!](#)

This Changes Everything

With a remarkably innovative pinch-swipe-zoom touchscreen user interface, the industry's largest high-definition display, and 4, 6, or 8 FlexChannel™ inputs that let you measure one analog or eight digital signals, the 5 Series MSO is ready for today's toughest challenges, and tomorrow's too. It sets a new standard for performance, analysis, and overall user experience.

[LEARN MORE](#)



Sampling Oscilloscopes – DC to 80 GHz

For very high speed signal analysis, both electrical and optical, our sampling oscilloscopes support jitter and noise analysis with ultra-low jitter acquisitions. They also perform TDR and S-parameter measurements.



Basic Oscilloscopes – 30 MHz to 200 MHz

For basic signal visualization and more, these instruments are solid performers with ample supporting materials, and generous warranties. Special features for education.



Battery Powered Oscilloscopes with Isolated Channels – 100 MHz to 200 MHz

Safely and easily make 4-channel floating measurements, including 3-phase power measurements



TDS Series Oscilloscopes – 50 MHz to 500 MHz

These capable industry-favorites have a large installed base, and thousands of companies rely on them as part of their test and measurement fleets. They continue to be fully supported.

MIXED SIGNAL AND MIXED DOMAIN OSCILLOSCOPES



	MSO/DPO2000B	MDO3000
Additional Resources		
Channels	2, 4 analog channels; 16 digital channels (MSO2000B)	2, 4 analog channels; 16 digital channels (MDO3MSO option) 1 spectrum analyzer input 1 Arbitrary/Function Generator (MDO3AFG option)
Bandwidth	70 MHz to 200 MHz	100 MHz to 1 GHz
Spectrum Analyzer Frequency Range	—	Standard: 9 kHz to Analog Bandwidth Optional: 9 kHz to 3 GHz
Sample Rate	1 GS/s (analog); 1 GS/s (digital, only 1 pod); 500 MS/s (digital, both pods)	2.5 GS/s to 5 GS/s (analog); 121.2 ps (8.25 GS/s) MagniVu™ (digital)
Max Record Length	1 Mpoints	10 Mpoints
Trigger Types	Edge, Logic, Pulse Width, Runt, Setup and Hold, Rise/Fall Time, Video, I²C*, SPI*, CAN*, LIN*, RS-232/422/485/UART*, Parallel (MSO2000B) *Optional	Edge, Sequence, Logic, Pulse Width, Runt, Timeout, Setup and Hold, Rise/Fall Time, Video, Extended Video, I²C*, SPI*, CAN FD*, CAN*, LIN*, FlexRay*, RS-232/422/485/UART*, I²S/LJ/RJ/TDM*, MIL-STD-1553*, ARINC 429, USB 2.0*, Parallel (with MDO3MSO option) *Optional
Optional Serial Bus Decode and Analysis	DPO2AUTO: CAN and LIN DPO2COMP: RS-232/422/485/UART DPO2EMBD: I²C, SPI DPO2BND: Includes DPO2AUTO, DPO2COMP, DPO2EMBD	MDO3AERO: ARINC 429, MIL-STD-1553 MDO3AUDIO: I²S, LJ, RJ, TDM MDO3AUTO: CAN FD, CAN and LIN MDO3COMP: RS-232/422/485/UART MDO3EMBD: I²C, SPI MDO3FLEX: FlexRay MDO3USB: USB2.0 MDO3BND: Enables MDO3AERO, MDO3AUDIO, MDO3AUTO, MDO3COMP, MDO3EMBD, MDO3FLEX, MDO3LMT, MDO3PWR, MDO3USB
Connectivity	USB Host, USB Device, GPIB*, Optional DPO2CONN Module: LAN (10/100 Base-T Ethernet) and Video Out *Optional	USB Host (x2), USB Device, LAN (10/100 Base-T Ethernet, LXI Core 2011 Compliant), Video Out, GPIB* *Optional
Waveform Math and Analysis	29 Automated Measurements, Waveform and Screen Cursors: Arithmetic Waveform Math, FFT	44 Automated Measurements, Waveform and Screen Cursors, Advanced Math, FFT, Measurement Statistics, Waveform Histograms Optional: MDO3PWR: Power Analysis MDO3LMT: Limit/mask test MDO3BND: Enables MDO3AERO, MDO3AUDIO, MDO3AUTO, MDO3COMP, MDO3EMBD, MDO3FLEX, MDO3LMT, MDO3PWR, MDO3USB
Software	PC communications software: OpenChoice® Desktop	PC Communications Software: OpenChoice® Desktop
Upgrade	Add serial bus triggering and decode	<ul style="list-style-type: none"> • Increase bandwidth • Add Arbitrary/Function generator • Add 16 digital channels • Increase spectrum analyzer maximum frequency to 3 GHz • Add measurements and analysis (power, limit/mask) • Add serial bus triggering and decode • Add security for password control of ports and firmware updates

MIXED SIGNAL AND MIXED DOMAIN OSCILLOSCOPES




MDO4000C	
Additional Resources	
Channels	4 analog channels; 16 digital channels (with MDO4MSO option); 1 spectrum analyzer input (with SA3 or SA6 option); 1 Arbitrary/Function Generator (with MDO4AFG option)
Bandwidth	200 MHz to 1 GHz
Spectrum Analyzer Frequency Range	Optional: 9 kHz - 3 GHz or 9 kHz - 6 GHz
Sample Rate	2.5 GS/s to 5 GS/s (analog); 60.6 ps (16.5 GS/s) MagniVu™ (digital)
Max Record Length	20 Mpoints
Trigger Types	RF Power Level**, Edge, Sequence, Logic, Pulse Width, Runt, Timeout, Setup and Hold, Rise/Fall Time, Video, Extended Video*, I²C*, SPI*, USB*, Ethernet*, CAN FD*, CAN*, LIN*, FlexRay*, RS-232/422/485/UART*, I²S/LJ/RJ/TDM*, MIL-STD-1553*, ARINC 429, Parallel* <small>**With optional MDO4TRIG module, RF power level can be used as source for Pulse Width, Timeout, Runt, Logic, Sequence</small>
Optional Serial Bus Decode and Analysis	DPO4AERO: ARINC 429, MIL-STD-1553 DPO4AUDIO: I²S, LJ, RJ, TDM DPO4AUTO: CAN FD, CAN and LIN DPO4AUTOMAX: CAN FD, CAN, LIN and FlexRay DPO4COMP: RS-232/422/485/UART DPO4EMBD: I²C, SPI DPO4ENET: 10Base-T, 100Base-TX Ethernet DPO4USB: USB DPO4BND: Enables DPO4AERO, DPO4AUDIO, DPO4AUTO, DPO4COMP, DPO4EMBD, DPO4ENET, DPO4LMT, DPO4PWR, DPO4USB, DPO4VID
Connectivity	USB Host (x4), USB Device, LAN (10/100/1000 Base-T Ethernet, LXI Core 2011 Compliant), Video Out, GPIB* *Optional
Waveform Math and Analysis	44 Automated Measurements, Waveform and Screen Cursors, Spectrum Math, FFT, Advanced Math, Measurement Statistics, Waveform Histograms Optional: DPO4LMT: Limit and Mask Testing MDO4TRIG: Adv. RF Power Level Trigger DPO4PWR: Power Analysis DPO4VID: HDTV and Custom Triggering DPO4BND: Enables DPO4AERO, DPO4AUDIO, DPO4AUTO, DPO4COMP, DPO4EMBD, DPO4ENET, DPO4LMT, DPO4PWR, DPO4USB, DPO4VID
Software	PC Communications Software: OpenChoice® Desktop Vector Signal Analysis Software: SignalVu-PC
Upgrade	<ul style="list-style-type: none"> • Increase bandwidth • Add Arbitrary/Function Generator • Add 16 digital channels • Add or upgrade spectrum analyzer channel • Add measurements & analysis (power, limit/mask, video, RF trigger) • Add serial bus triggering and decode • Add security for password control of ports and firmware updates

ADVANCED SIGNAL ANALYSIS OSCILLOSCOPES



	5 SERIES MSO	6 SERIES MSO
Additional Resources		
Channels	4, 6, or 8 FlexChannel® inputs; 8 digital channels per FlexChannel input (optional); 1 Arbitrary/Function Generator (with 5-AFG option)	4 FlexChannel® inputs; 8 digital channels per FlexChannel input (optional); 1 Arbitrary/Function Generator (with 6-AFG option)
Bandwidth	350 MHz to 2 GHz	1 GHz to 8 GHz
Sample Rate	6.25 GS/s (analog); 6.25 GS/s (digital)	25 GS/s / channel (analog); 25 GS/s / channel (digital)
Max Record Length	Up to 125 Mpoints	Up to 250 Mpoints
Trigger Types	Edge, Sequence, Logic, Pulse Width, Runt, Visual Trigger, Timeout, Window, Setup and Hold, Rise/Fall Time, I²C*, SPI*, USB*, Ethernet*, CAN*, CAN FD*, LIN*, FlexRay*, RS-232/422/485/UART*, I²S/LJ/RJ/ TDM*, MIL-STD-1553*, ARINC 429*, SENT*, SPMI*, Parallel *Optional	Edge, Sequence, Logic, Pulse Width, Runt, Visual Trigger, Timeout, Window, Setup and Hold, Rise/Fall Time, I²C*, SPI*, USB*, Ethernet*, CAN*, CAN FD*, LIN*, FlexRay*, RS-232/422/485/UART*, I²S/LJ/RJ/ TDM*, MIL-STD-1553*, ARINC 429*, SENT*, SPMI*, Parallel *Optional
Optional Serial Bus Decode and Analysis	5-SRAERO: MIL-STD-1553, ARINC 429 5-SRAUDIO: I²S, LJ, RJ, TDM 5-SRAUTO: CAN, CAN FD, LIN, FlexRay 5-SRAUTOPEN: SENT 5-SRCOMP: RS-232/422/485/UART 5-SREMBD: I²C, SPI 5-SRENET: Ethernet 5-SRPM: SPMI 5-SRUSB2: USB 2.0	6-SRAERO: MIL-STD-1553, ARINC 429 6-SRAUDIO: I²S, LJ, RJ, TDM 6-SRAUTO: CAN, CAN FD, LIN, FlexRay 6-SRAUTOPEN: SENT 6-SRCOMP: RS-232/422/485/UART 6-SREMBD: I²C, SPI 6-SRENET: Ethernet 6-SRPM: SPMI 6-SRUSB2: USB 2.0
Connectivity	USB Host (x7), USB 3.0 Device, LAN (10/100/1000 Base-T Ethernet, 1.4 LXI Core 2011 Compliant), Display Port, DVI-D, Video Out	USB Host (x7), USB 3.0 Device, LAN (10/100/1000 Base-T Ethernet, 1.4 LXI Core 2011 Compliant), Display Port, DVI-D, Video Out
Waveform Math and Analysis	36 Automated Measurements, Waveform and Screen Cursors, Arithmetic Waveform Math, FFT, Advanced Math, Measurement Statistics Optional: 5-CMAUTOEN: Automotive Ethernet Compliance; 5-CMUSB2: USB 2.0 Compliance; 5-DJA: Advanced Jitter and Eye Diagram Analysis; 5-PWR: Advanced Power Measurements.	36 Automated Measurements, Waveform and Screen Cursors, Arithmetic Waveform Math, FFT, Advanced Math, Measurement Statistics Optional: 6-CMAUTOEN: Automotive Ethernet Compliance; 6-CMUSB2: USB 2.0 Compliance; 6-DJA: Advanced Jitter and Eye Diagram Analysis; 6-PWR: Advanced Power Measurements
Software	Optional: TekScope Anywhere™	Optional: TekScope Anywhere™
Upgrade	<ul style="list-style-type: none"> • Add serial bus triggering and decode • Add serial bus compliance testing • Add digital channels with each TLP058 logic probe • Add extended record length, up to 125 Mpoints • Add advanced measurements and analysis (power, jitter) 	<ul style="list-style-type: none"> • Add serial bus triggering and decode • Add serial bus compliance testing • Add digital channels with each TLP058 logic probe • Add extended record length, up to 250 Mpoints • Add advanced measurements and analysis (power, jitter)

ADVANCED SIGNAL ANALYSIS OSCILLOSCOPES



	MSO/DP05000B	DP07000C
Additional Resources		
Channels	4 analog channels; 16 digital channels (MSO5000B)	4 analog channels
Bandwidth	350 MHz to 2 GHz	500 MHz to 3.5 GHz
Sample Rate	5 GS/s to 10 GS/s (analog); 60.6 ps (16.5 GS/s) MagniVu™ (digital)	10 GS/s to 40 GS/s
Max Record Length	Up to 250 Mpoints	Up to 500 Mpoints
Trigger Types	Edge, Sequence, Logic, Pulse Width, Glitch, Runt, Timeout, Transition, Setup and Hold, Rise/Fall Time, Video, I²C*, SPI*, USB (Low, Full, High)*, RS-232/422/485/UART*, USB*, Ethernet*, CAN*, LIN*, FlexRay*, MIL-STD-1553*, Parallel (MSO5000B), Visual Trigger *Optional	Pinpoint™ Triggering, Edge, Glitch, Pulse Width, Runt, Time-out, Transition, Setup/Hold, Pattern, State, Window, Trigger Delay (by Time and by Event), I²C*, SPI*, USB (Low, Full)*, RS-232/422/485/UART*, I²C*, SPI*, USB*, Ethernet*, CAN*, LIN*, FlexRay*, RS-232/422/485/UART*, MIL-STD-1553*, Visual Trigger *Optional
Optional Serial Bus Decode and Analysis	SR-AERO: MIL-STD-1553 SR-AUTO: CAN/LIN/FlexRay SR-COMP: RS-232/422/485/UART SR-DPHY: MIPI D-PHY SR-EMBD: I²C, SPI SR-ENET: 10/100Base-T Ethernet SR-USB: USB	SR-AERO: MIL-STD-1553 SR-AUTO: CAN/LIN/FlexRay SR-COMP: RS-232/422/485/UART SR-DPHY: MIPI D-PHY SR-EMBD: I²C, SPI SR-ENET: 10/100Base-T Ethernet SR-PCIE: PCI Express SR-USB: USB
Connectivity	USB Host (x6), USB Device, LAN (10/100/1000 Base-T Ethernet, LXI Class C Compliant), Video Out, GPIB* *Optional	USB Host (x5), LAN (10/100/1000 Base-T Ethernet, LXI Class C Compliant), GPIB, eSATA, DVI, VGA
Waveform Math and Analysis	53 Automated Measurements, Waveform and Screen Cursors, Arithmetic and Advanced Waveform Math, FFT, Measurement Statistics, Waveform Histograms, Waveform Limit Testing Optional: BRR: BroadR-Reach Compliance Test; DDRA: DDR Memory Bus Analysis; DJA: DPOJET Advanced Jitter and Eye Diagram Analysis; ET3: Ethernet Compliance Test Solution; MTM: Mask Testing; PWR: Power Analysis; SignalVu Vector Signal Analysis; USB2: USB Compliance Test Solution; MOST: MOST 50/150 Compliance Test Solution; HSIC: HSIC Electrical Validation; USBPWR: USB Power Adapter/ EPS Compliance Automated Test Solution	53 Automated Measurements, Waveform and Screen Cursors, Arithmetic and Advanced Waveform Math, FFT, Measurement Statistics, Waveform Histograms, Waveform Limit Testing Optional: BRR: BroadR-Reach Compliance Test; DDRA: DDR Memory Bus Analysis; DJA: DPOJET Advanced Jitter and Eye Diagram Analysis; D-PHY: MIPI D-PHY Essentials; ET3: Ethernet Compliance Test Solution; MTM: Mask Testing; PWR: Power Analysis; SignalVu Vector Signal Analysis; USB2: USB Compliance Test Solution; MOST: MOST 50/150 Compliance Test Solution; HSIC: HSIC Electrical Validation; USBPWR: USB Power Adapter/ EPS Compliance Automated Test Solution
Software	Optional: TekScope Anywhere™	Optional: TekScope Anywhere™
Upgrade	<ul style="list-style-type: none"> • Add 16 digital channels • Add extended record length, up to 250 Mpoints • Add serial bus compliance testing • Add measurements and analysis (power, jitter, mask, RF) • Add serial bus triggering and decode 	<ul style="list-style-type: none"> • Trade in older DPO7000 Series models for credit toward the newest DPO7000C version (50% credit of the old scope price) • Add extended record length, up to 500 Mpoints • Add serial bus compliance testing • Add measurements and analysis (power, jitter, mask, RF) • Add serial bus triggering and decode

ADVANCED SIGNAL ANALYSIS OSCILLOSCOPES



	MSO/DPO70000	DPO70000SX
Additional Resources		
Channels	4 analog channels; 16 digital channels (MSO70000)	2 or 4 analog channels
Bandwidth	4 GHz to 33 GHz Analog	23 GHz to 70 GHz
Sample Rate	25 GS/s to 100 GS/s (analog); 80 ps (12.5 GS/s) (digital)	50 GS/s to 200 GS/s
Max Record Length	Up to 1 Gpoints	Up to 1 Gpoints
Trigger Types	Pinpoint™ Triggering, Edge, Glitch, Pulse Width, Runt, Time-out, Transition, Setup/Hold, Pattern, State, Window, Trigger Delay (by Time and by Event), I²C*, SPI*, USB (Low, Full)*, RS-232/422/485/UART*, Serial Pattern*, Visual Trigger* *Optional	Pinpoint™ Triggering, Edge, Glitch, Pulse Width, Runt, Time-out, Transition, Setup/Hold, Pattern, State, Window, Trigger Delay (by Time and by Event), Visual Trigger* *Optional
Optional Serial Bus Decode and Analysis	SR-AERO: MIL-STD-1553; SR-AUTO: CAN/LIN/FlexRay; SR-COMP: RS-232/422/485/UART; SR-DPHY: MIPI D-PHY; SR-EMBD: I²C, SPI; SR-ENET: 10/100Base-T Ethernet SR-PCIE: PCI Express; SR-USB: USB; SR-810B: 8b/10b; 10G-KR: 10GBASE-KR/KR4	SR-COMP: RS-232/422/485/UART; SR-EMBD: I²C, SPI; SR-ENET: 10/100Base-T Ethernet SR-PCIE: PCI Express; SR-USB: USB; SR-810B: 8b/10b
Connectivity	USB Host (x5), LAN (10/100/1000 Base-T Ethernet, LXI Class C Compliant), GPIB, eSATA, DVI, VGA	USB2.0 Host (4 on front)/3.0 Host (4 on rear), USB Device, LAN (10/100/1000 Base-T Ethernet, LXI Class C Compliant), DVI, VGA, DisplayPort (2)
Waveform Math and Analysis	53 Automated Measurements, Waveform and Screen Cursors, Arithmetic and Advanced Waveform Math, FFT, Measurement Statistics, Waveform Histograms Optional: BRR: BroadR-Reach Compliance Test; DDR Memory Bus Analysis; DPOJET Advanced Jitter and Eye Diagram Analysis; Ethernet Compliance; Waveform Limit Testing; Mask Testing; Power Analysis; USB2 and USB3 Compliance and Analysis; USB Power Adapter/ EPS Compliance Automated Test Solution; MOST 50/150 Compliance Test; SignalVu Vector Signal Analysis; HDMI Compliance Test; HSIC Electrical Validation; MIPI D-PHY and M-PHY Characterization and Analysis; SAS Testing; SFP+ Compliance and Debug; Serial Data Link Analysis; 10G-KR Compliance and Debug; PCIe Compliance and Debug; Thunderbolt Characterization, Compliance and Debug; UHS Measurements; PAM4 Transmitter Analysis Software; SignalCorrect Cable, Channel and Probe Compensation Software	53 Automated Measurements, Waveform and Screen Cursors, Arithmetic and Advanced Waveform Math, FFT, Measurement Statistics, Waveform Histograms Optional: DPOJET Noise, Jitter and Eye Analysis Tools; Frequency Counter-Timer; PAM4 Transmitter Analysis Software; Serial Data Link Analysis; 10G/40G/100G KR4/CR4 Transmitter Compliance; DDR Memory Bus Analysis; DisplayPort 1.2/1.4 Test Software; MIPI D-PHY Transmitter Debug and Compliance Test Solution; EDP Compliance Test Package; Ethernet Compliance Testing; Fiber Channel Essentials; HDMI 2.0 Analysis and Compliance; High Speed Serial Link Training Analysis; HDMI Compliance Testing; MIPI M-PHY Debug and Compliance Test; NBASE-T TekExpress Conformance and Debug Software; PCI Express Gen1/2/3/4 TekExpress Compliance/Debug; Power Measurement and Analysis Software; SAS-3 Tx Compliance Test; SATA PHY Transmitter Test; SignalCorrect Cable, Channel, and Probe Compensation Software; SFP+ Compliance and Debug Solution; Embedded Serial Triggering and Analysis (I²C, SPI); USB 2.0/3.0/3.1 Automated Compliance Test; SignalVu Vector Signal Analysis
Software	Optional: TekScope Anywhere™	Optional: TekScope Anywhere™
Upgrade	<ul style="list-style-type: none"> • Increase bandwidth • Add 16 digital channels • Upgrade older platforms to the latest platforms • Add extended record length, up to 1 Gpoints • Add serial bus compliance testing • Add measurements and analysis (jitter, DDR, mask, RF) • Add serial bus triggering and decode 	<ul style="list-style-type: none"> • Increase bandwidth • Upgrade older platforms to the latest platforms • Add extended record length, up to 1 G points • Add measurements and analysis (jitter, mask, RF)

BASIC OSCILLOSCOPES



	TBS1000	TBS1000B/ TBS1000B-EDU	TBS2000
Additional Resources			
Channels	4	2	2, 4
Bandwidth	60 MHz to 150 MHz	30 MHz* to 200 MHz * 30 MHz TBS1032B available in North America and Europe	70 MHz, 100 MHz
Sample Rate	1 GS/s	500 MS/s to 2 GS/s	1 GS/s
Max Record Length	2.5 k points	2.5 k points	20 M points
Trigger Types	Edge, Pulse (width), Video	Edge, Pulse (width), Video	Edge, Pulse (width), Runt
Optional Serial Bus Decode and Analysis	—	—	—
Connectivity	USB Host, USB Device, Optional: GPIB	USB Host, USB Device, Optional: GPIB	USB Host, Wi-Fi adapter support, 10/100 Base-T Ethernet port
Waveform Math and Analysis	16 Automated Measurements, Arithmetic Waveform Math, FFT, Waveform Limit Testing, Automated Datalogging	34 Automated Measurements, Arithmetic Waveform Math, FFT, Dual-Channel Frequency Counter, Waveform Limit Testing*, TrendPlot™ function*, Automated Datalogging* * Not available on EDU models	32 Automated Measurements, Arithmetic Waveform Math, FFT, Frequency Counter
Software	PC Communications Software: OpenChoice® Desktop, Educator Classroom and Lab Resource CD	PC Communications Software: OpenChoice® Desktop Software, PC Courseware Editor Tool, Product Documentation and Lab Resource CD	PC Communications Software: OpenChoice® Desktop, PC Courseware Editor
Battery Operation	—	—	—



Teaching Oscilloscopes

TBS2000 and TBS1000B-EDU Oscilloscopes have unique features designed to meet the needs of schools and universities. They use an innovative courseware system that enables educators to build teaching materials into the oscilloscope. Along with a powerful PC Courseware Editor Tool and a courseware website, these oscilloscopes support a complete education ecosystem that makes it easier to teach engineering and easier to learn.

[LEARN MORE](#)

LOW PROFILE AND SAMPLING OSCILLOSCOPES



5 SERIES MSO LOW PROFILE

DSA8300

Additional Resources

Channels	8 FlexChannel® inputs; 8 digital channels per FlexChannel input (optional); 1 Arbitrary/Function Generator (5-AFG option); Aux trigger	Six modules support up to 8 single-ended or 4 differential channels and/or 2 optical channels
Bandwidth	1 GHz	Up to 70+ GHz Electrical bandwidth and 80+ Optical bandwidth modules available with intrinsic jitter as low as <100 fs RMS
Sample Rate	6.25 GS/s (analog); 6.25 GS/s (digital)	300 ks/s Maximum sample rate
Max Record Length	125 Mpoints	50 to 16,000 per channel native record length; with up to 1M points when using available IConnect Signal Integrity Software, 10M samples (100k unit intervals, 100 samples per unit interval) when equipped with available 80SJNB Jitter, Noise and BER Analysis software
Trigger Types	Edge, Sequence, Logic, Pulse Width, Runt, Visual Trigger, Timeout, Window, Setup and Hold, Rise/Fall Time, I²C*, SPI*, USB*, Ethernet*, CAN*, CAN FD*, LIN*, FlexRay*, RS-232/422/485/UART*, I²S/LJ/RJ/TDM*, MIL-STD-1553*, ARINC 429*, SENT*, SPMI*, Parallel *Optional	Clock Input/Prescale Trigger, TDR clock (generated internally), Clock Recovery from Optical Sampling modules and Electrical Clock Recovery modules, and Phase Reference time base supports acquisitions Free Run mode and Trigger Direct Input for <100 fs RMS intrinsic jitter typical
Optional Serial Bus Decode and Analysis	5-SRAERO: MIL-STD-1553, ARINC 429 5-SRAUDIO: I²S, LJ, RJ, TDM 5-SRAUTO: CAN, CAN FD, LIN, FlexRay 5-SRAUTOSEN: SENT 5-SRCOMP: RS-232/422/485/UART 5-SREMBD: I²C, SPI 5-SRENET: Ethernet 5-SRPM: SPMI 5-SRUSB2: USB 2.0	80SJNB Jitter, Noise, BER, Serial Data Link and PAM4 Analysis Software; IConnect Signal Integrity Software; 100GBASE-SR4 Transmitter and Dispersion Eye Closure (TDEC) Automation Test Solution
Connectivity	USB Host (x6), USB 3.0 Device, LAN (10/100/1000 Base-T Ethernet, 1.4 LXI Core 2011 Compliant), DisplayPort, DVI-D, Video Out	3 USB 2.0 Port(s) connector on the front panel, 4 USB 2.0 Ports on the rear panel; LAN PORT, RJ-45 connector, supports 10BASE-T, 100BASE-T, 1000BASE-T on rear panel; 1 Serial Port, DB-9 COM1, COM2 ports; 1 DVI IEEE488.2 connector on rear panel; 1 DVI connector, female on rear panel, DVI to VGA 15-pin D-sub connector adapter provided; PS2 Serial Ports Mouse and keyboard inputs; Audio Ports 1/8 in. microphone input and line output
Waveform Math and Analysis	36 Automated Measurements, Waveform and Screen Cursors, Arithmetic Waveform Math, FFT, Advanced Math, Measurement Statistics Optional: 5-DJA: Advanced Jitter and Eye Diagram Analysis; 5-PWR: Advanced Power Measurements	Over 120 automated measurements include RZ, NRZ, and pulse signal types, and the following measurement types, plus 8 math waveforms using the following math functions: Add, Subtract, Multiply, Divide, Average, Differentiate, Exponential, Integrate, Natural Log, Log, Magnitude, Min, Max, Square Root, and Filter. In addition, measurement values can be utilized as scalars in math waveform definitions; Mask support for many applications, standard masks are available as predefined, built-in masks; Automated Masked Margin based on Mask Hit Ratio as required by many standards.
Software	Optional: TekScope Anywhere™	Windows® 7 Ultimate (32-bit) Operating System; IConnect Signal Integrity Software for frequency domain analysis, S-parameter measurements, and impedance characterization 80SJNB Jitter, Noise, BER, and Serial Link analysis including Cross-Talk aware TJ (BUJ and PAM4 Analysis); 80SJARB Jitter Analysis of Arbitrary Data with J2-J9 measurements, and support for pattern lengths to PRBS31; 100GBASE-SR4 (IEEE 802.3bm) optical transmitter characterization measurements, including TDEC, signaling rate, Average Launch Power, OMA, ER, Transmitter Eye Mask
Upgrade	<ul style="list-style-type: none"> • Add serial bus triggering and decode • Add digital channels with each TLP058 logic probe • Add advanced measurements and analysis 	<ul style="list-style-type: none"> • Modular architecture lets you add channels or bandwidth • Add TDR, optical and electrical standards support • Add advanced analysis, compliance test, frequency domain analysis software • Add clock recovery trigger pickoff (CRTP) to select optical modules • Enhance system jitter floor performance to <100 fs RMS

BATTERY POWERED OSCILLOSCOPES WITH ISOLATED CHANNELS AND TDS SERIES OSCILLOSCOPES



	THS3000	TPS2000B	TDS2000C	TDS3000C
Additional Resources				
Channels	4 (isolated)	2, 4 (isolated)	2, 4	2, 4
Bandwidth	100 MHz to 200 MHz	100 MHz to 200 MHz	50 MHz to 200 MHz	100 MHz to 500 MHz
Sample Rate	2.5 GS/s to 5 GS/s	1 GS/s to 2 GS/s	500 MS/s to 2 GS/s	1.25 GS/s to 5 GS/s
Max Record Length	10 k points	2.5 k points	2.5 k points	10 k points
Trigger Types	Edge, Pulse (width), Event, Video, Non-interlaced	Edge, Pulse (width), Video	Edge, Pulse (width), Video	Edge, Logic (Pattern, State), Pulse (Glitch, Width, Runt, Slew Rate), Video, Optional: Extended Video, Comm
Optional Serial Bus Decode and Analysis	—	—	—	—
Connectivity	USB Host, USB Device	RS-232 (includes RS-232-to-USB Host Serial Cable), Centronics, CompactFlash	USB Host, USB Device, Optional: GPIB	USB Host, LAN (10Base-T Ethernet) Optional: TDS3GV Module: GPIB, RS-232, and Video Out
Waveform Math and Analysis	21 Automated Measurements, Arithmetic Waveform Math, FFT Optional: TPS2PWR1: Power Measurement and Analysis	11 Automated Measurements, Arithmetic Waveform Math, FFT Optional: TPS2PWR1: Power Measurement and Analysis	16 Automated Measurements, Arithmetic Waveform Math, FFT, Waveform Limit Testing, Automated Datalogging	25 Automated Measurements, Arithmetic Waveform Math, FFT Optional: TDS3LIM: Limit Testing, TDS3TMT: Telecom Mask Testing, TDS3VID: HDTV & Custom Video Triggering
Software	PC Communications Software: OpenChoice® Desktop	PC Communications Software: OpenChoice® Desktop	PC Communications Software: OpenChoice® Desktop	PC Communications Software: OpenChoice® Desktop
Battery Operation	One THSBAT Battery Pack Included Standard	One TPSBAT Battery Pack Included Standard	—	Requires Optional TDS3BATC Battery Pack

INTERACTIVE PROBE SELECTOR TOOL

Need help finding the right probe for your application? The online Tektronix Probe Selector Tool will guide you through a few easy questions to match your need to the right probe. Visit us anytime, anywhere at: tektronix.com/probes.



LEARN MORE
ON THE GO!

Tektronix® SOLUTIONS PRODUCTS SERVICES & SUPPORT 1-800-833-9200 BUY | QUOTE Login

Probe Selector Tool

Select a measurement

- Current Probe
- High Voltage Differential Probes
- High Voltage Single Ended Probes
- Logic Analyzer Probe
- Low Voltage Differential Probes
- Low Voltage Single Ended Probes
- Isolated Measurement Systems
- Passive Probe

Select an instrument

- DPO7000C
- DPO70000SX
- MDO3000
- MDO4000C
- MSO/DPO2000B
- MSO/DPO3000
- MSO/DPO4000
- MSO/DPO5000
- MSO/DPO70000
- TBS1000
- NEWI TBS2000
- TDS2000
- TDS3000
- TDS5000
- TPS2000

APPLY


Recommended Probes:

<input type="checkbox"/> Compare  TPP1000 <small>+View Larger</small>	LIST PRICE US \$996	Bandwidth 1 GHz	Input Range 300 V CAT II	CONFIGURE & QUOTE
>> View Compatible Instruments				
<input type="checkbox"/> Compare  TPP0502 <small>+View Larger</small>	LIST PRICE US \$652	Bandwidth 500 MHz	Input Range 300 V CAT II	CONFIGURE & QUOTE
>> View Compatible Instruments				

CONTACT US

DOWNLOADS

IsoVu® Isolated Probes See What's Been Hidden - Until Now



Common mode interference often causes engineers to design, debug, evaluate, and optimize "blind." Revolutionary IsoVu™ technology uses optical communications and power-over-fiber for complete galvanic isolation. When combined with an oscilloscope equipped with the TekVPI interface, it is the first, and only, measurement system capable of accurately resolving high bandwidth differential signals in the presence of large common mode voltage.

LEARN MORE

OSCILLOSCOPE PROBES AND ACCESSORIES

Tektronix probes and accessories are perfectly matched to our industry-leading oscilloscopes.

With over 100 choices available, you will find the probe you need. Need help finding the right probe for your application? The online Tektronix Probe Selector Tool will guide you through a few easy questions to match your need to the right probe.



LEARN MORE
ON THE GO!



Isolated Probes

- High-resolution measurements in the presence of common mode signals or noise
- Up to 1 GHz bandwidth
- Complete galvanic isolation
- 1 Million to 1 (120 dB) of common mode rejection at 100 MHz

<http://www.tek.com/isolated-measurement-systems>



Low Voltage Differential Probes

- Bandwidth up to 33 GHz
- Easily measure differential signals
- Low input capacitance: down to < 0.3 pF
- High common mode rejection ratio (CMRR)
- Wide range of probe tips for easier circuit access

<tek.com/differential-probe-low-voltage>



High Voltage Differential Probes

- Dynamic range to ± 6000 V
- Bandwidth up to 200 MHz
- Most extensive set of probe accessories

<tek.com/differential-probe-high-voltage>



Current Probes

- Easy to use and accurate AC/DC current measurements
- DC up to 2 GHz
- Amplitude measurements from 1 mA to 2,000 A
- Split core and solid core construction

<tek.com/current-probe>



Passive Probes

- Best-in-class bandwidth up to 1 GHz
- Best-in-class input capacitance as low as 3.9 pF, which minimizes probe loading effects
- Dynamic range to 300 V CAT II
- Rugged and reliable

<tek.com/passive-probe>



Low Voltage Single-ended Probes

- Bandwidth up to 4 GHz
- True signal reproduction and fidelity
- Low input capacitance: down to < 0.8 pF
- Small, compact probe heads for probing small geometry circuit elements

<tek.com/low-voltage-probe-single-ended>



High Voltage Single-ended Probes

- Bandwidth up to 800 MHz
- Dynamic range to 2500 V
- Best-in-class probe loading with input capacitance as low as 1.8 pF

<tek.com/high-voltage-probe-single-ended>



Optical

- Broad Wavelength Response: 500 to 950 nm or 1100 to 1700 nm
- High-bandwidth DC up to 1.2 GHz
- High Gain 1 V/mW
- Low Noise <1 pW/ $\sqrt{\text{Hz}}$
- DC to 33 GHz (DPO7OE1)

Optical Probe DPO7OE2
DC to 59 GHz

<tek.com/optical-probe>

SERIAL SUPPORT BY MSO/DPO PRODUCT SERIES AND REQUIRED OPTIONAL SOFTWARE

MSO/DPO7000C/DX Series				DPO7000C Series
	Decode & Search	Serial Trigger	Compliance Test	Decode & Search
Embedded	I ² C	SR-EMBD	SR-EMBD	-
	SPI	SR-EMBD	SR-EMBD	-
	RS-232/UART	SR-COMP	SR-COMP	-
	SPMI	-	-	-
	I ² S	-	-	-
Transportation	CAN	SR-AUTO	SR-AUTO	-
	CAN FD	-	-	-
	LIN	SR-AUTO	SR-AUTO	-
	FlexRay	SR-AUTO	SR-AUTO	-
	MOST	-	-	MOST
	SENT	-	-	-
	Automotive Ethernet	-	-	BRR
	ARINC 429	-	-	-
	MIL-STD-1553B	SR-AERO	SR-AERO	-
Computer / Peripherals	USB 2.0	SR-USB	SR-USB (LS, FS)	USB2
	USB 3.0	SR-USB	-	USB3, TEKEXP Opt. USB-RMT, USB-TX
	MIPI D-PHY	SR-DPHY	-	D-PHY, TEKEXP Opt. D-PHYTX
	MIPI M-PHY	-	-	M-PHY, M-PHYTX, M-PHYRX
	PCIe	SR-PCIE	-	PCE3
	DiiVA	-	-	TEKEXP Opt. DIIVA
	DisplayPort	-	-	DP12, TEKEXP Opt. DP-SINK
	HDMI	-	-	HT3, HT3DS
	MHL	-	-	MHD
	SATA	-	-	SATA-RSG, SATA-TSG
Memory	SAS3	-	-	SAS3, SAS-TSG, SAS-TSGW
	Thunderbolt	-	-	TBT-TX
	UHS-II	-	-	UHS2
	DDR	-	-	DDRA, DDR-LP4
	Ethernet	SR-ENET	-	ET3, XBGT2, NBASET
	Comm. Mask Testing	-	-	MTH
	Fibre Channel	-	-	FC-16G
Datacom	10GBASE-T KR	-	-	10G-KR
	SFP+	-	-	SFP-TX, SFP-WDP
	Custom Serial	SR-CUST	-	-
	8b/10b	SR-810B	-	-
	NRZ Serial	-	ST6G	-
Advanced Analysis	PAM4	-	-	PAM4
	Serial Data Link Analysis	-	-	SDLA64
	Jitter & Eye Diagram Analysis	-	-	DJA (DJE incl. std), DJAN
				DJA (DJE incl. std), DJAN

SERIAL SUPPORT BY MSO PRODUCT SERIES AND REQUIRED OPTIONAL SOFTWARE

		5 Series MSO			6 Series MSO		
	Serial Standard	Decode & Search	Serial Trigger	Compliance Test	Decode & Search	Serial Trigger	Compliance Test
Embedded	I ² C	5-SREMBD	5-SREMBD	-	6-SREMBD	6-SREMBD	-
	SPI	5-SREMBD	5-SREMBD	-	6-SREMBD	6-SREMBD	-
	RS-232/UART	5-SRCOMP	5-SRCOMP	-	6-SRCOMP	6-SRCOMP	-
	SPMI	5-SRPM	5-SRPM	-	6-SRPM	6-SRPM	-
	I ² S	5-SRAUDIO	5-SRAUDIO	-	6-SRAUDIO	6-SRAUDIO	-
Transportation	CAN	5-SRAUTO	5-SRAUTO	-	6-SRAUTO	6-SRAUTO	-
	CAN FD	5-SRAUTO	5-SRAUTO	-	6-SRAUTO	6-SRAUTO	-
	LIN	5-SRAUTO	5-SRAUTO	-	6-SRAUTO	6-SRAUTO	-
	FlexRay	5-SRAUTO	5-SRAUTO	-	6-SRAUTO	6-SRAUTO	-
	MOST	-	-	-	-	-	-
	SENT	5-SRAUTOSEN	5-SRAUTOSEN	-	6-SRAUTOSEN	6-SRAUTOSEN	-
	Automotive Ethernet	-	-	5-CMAUTOEN	-	-	6-CMAUTOEN
	ARINC 429	5-SRAERO	5-SRAERO	-	6-SRAERO	6-SRAERO	-
	MIL-STD-1553B	5-SRAERO	5-SRAERO	-	6-SRAERO	6-SRAERO	-
	USB 2.0	5-SRUSB2	5-SRUSB2	5-CMUSB2	6-SRUSB2	6-SRUSB2	6-CMUSB2
Computer / Peripherals	USB 3.0	-	-	-	-	-	-
	MIPI D-PHY	-	-	-	-	-	-
	MIPI M-PHY	-	-	-	-	-	-
	PCIe	-	-	-	-	-	-
	DiiVA	-	-	-	-	-	-
	DisplayPort	-	-	-	-	-	-
	HDMI	-	-	-	-	-	-
	MHL	-	-	-	-	-	-
	SATA	-	-	-	-	-	-
	SAS3	-	-	-	-	-	-
	Thunderbolt	-	-	-	-	-	-
	UHS-II	-	-	-	-	-	-
Memory	DDR	-	-	-	-	-	-
Datacom	Ethernet	5-SRENETH	5-SRENETH	-	6-SRENETH	6-SRENETH	-
	Comm. Mask Testing	-	-	-	-	-	-
	Fibre Channel	-	-	-	-	-	-
	10GBASE-T KR	-	-	-	-	-	-
	SFP+	-	-	-	-	-	-
Advanced Analysis	Custom Serial	-	-	-	-	-	-
	8b/10b	-	-	-	-	-	-
	NRZ Serial	-	-	-	-	-	-
	PAM4	-	-	-	-	-	-
	Serial Data Link Analysis	-	-	-	-	-	-
	Jitter & Eye Diagram Analysis	-	-	5-DJA	-	-	6-DJA

SERIAL SUPPORT BY MDO PRODUCT SERIES AND REQUIRED OPTIONAL SOFTWARE

MDO4000C Series				MDO3000 Series			
	Serial Standard	Decode & Search	Serial Trigger	Compliance Test	Decode & Search	Serial Trigger	Compliance Test
Embedded	I ² C	DPO4EMBD	DPO4EMBD	-	MD03EMBD	MD03EMBD	-
	SPI	DPO4EMBD	DPO4EMBD	-	MD03EMBD	MD03EMBD	-
	RS-232/UART	DPO4COMP	DPO4COMP	-	MD03COMP	MD03COMP	-
	SPMI	-	-	-	-	-	-
	I ² S	DPO4AUDIO	DPO4AUDIO	-	MD03AUDIO	MD03AUDIO	-
Transportation	CAN	DPO4AUTO	DPO4AUTO	-	MD03AUTO	MD03AUTO	-
	CAN FD	DPO4AUTO	DPO4AUTO	-	MD03AUTO	MD03AUTO	-
	LIN	DPO4AUTO	DPO4AUTO	-	MD03AUTO	MD03AUTO	-
	FlexRay	DPO4AUTOMAX	DPO4AUTOMAX	-	MD03FLEX	MD03FLEX	-
	MOST	-	-	-	-	-	-
	SENT	-	-	-	-	-	-
	Automotive Ethernet	-	-	-	-	-	-
	ARINC 429	DP04AERO	DP04AERO	-	-	-	-
	MIL-STD-1553B	DP04AERO	DP04AERO	-	MD03AERO	MD03AERO	-
Computer / Peripherals	USB 2.0	DPO4USB	DPO4USB	-	MD03USB	MD03USB	-
	USB 3.0	-	-	-	-	-	-
	MIPI D-PHY	-	-	-	-	-	-
	MIPI M-PHY	-	-	-	-	-	-
	PCIe	-	-	-	-	-	-
	DiiVA	-	-	-	-	-	-
	DisplayPort	-	-	-	-	-	-
	HDMI	-	-	-	-	-	-
	MHL	-	-	-	-	-	-
	SATA	-	-	-	-	-	-
	SAS3	-	-	-	-	-	-
	Thunderbolt	-	-	-	-	-	-
Memory	UHS-II	-	-	-	-	-	-
	DDR	-	-	-	-	-	-
Datacom	Ethernet	DPO4ENET	DPO4ENET	-	-	-	-
	Comm. Mask Testing	-	-	DPO4LMT	-	-	MD03LMT
	Fibre Channel	-	-	-	-	-	-
	10GBASE-T KR	-	-	-	-	-	-
	SFP+	-	-	-	-	-	-
Advanced Analysis	Custom Serial	-	-	-	-	-	-
	8b/10b	-	-	-	-	-	-
	NRZ Serial	-	-	-	-	-	-
	PAM4	-	-	-	-	-	-
	Serial Data Link Analysis	-	-	-	-	-	-
	Jitter & Eye Diagram Analysis	-	-	-	-	-	-

SERIAL SUPPORT BY MSO/DPO PRODUCT SERIES AND REQUIRED OPTIONAL SOFTWARE

MSO/DPO2000B Series				MSO/DPO5000B Series			
	Serial Standard	Decode & Search	Serial Trigger	Compliance Test	Decode & Search	Serial Trigger	Compliance Test
Embedded	I ² C	DPO2EMBD	DPO2EMBD	-	SR-EMBD	SR-EMBD	-
	SPI	DPO2EMBD	DPO2EMBD	-	SR-EMBD	SR-EMBD	-
	RS-232/UART	DPO2COMP	DPO2COMP	-	SR-COMP	SR-COMP	-
	SPMI	-	-	-	-	-	-
	I ² S	-	-	-	-	-	-
Transportation	CAN	DPO2AUTO	DP02AUTO	-	SR-AUTO	SR-AUTO	-
	CAN FD	-	-	-	-	-	-
	LIN	DPO2AUTO	DP02AUTO	-	SR-AUTO	SR-AUTO	-
	FlexRay	-	-	-	SR-AUTO	SR-AUTO	-
	MOST	-	-	-	-	-	MOST
	SENT	-	-	-	-	-	-
	Automotive Ethernet	-	-	-	-	-	BRR
	ARINC 429	MD03AERO	MD03AERO	-	SR-AERO	SR-AERO	-
	MIL-STD-1553B	-	-	-	SR-USB	SR-USB	USB2
Computer / Peripherals	USB 2.0	-	-	-	-	-	-
	USB 3.0	-	-	-	SR-DPHY	SR-DPHY	-
	MIPI D-PHY	-	-	-	-	-	-
	MIPI M-PHY	-	-	-	SR-PCIE	SR-PCIE	-
	PCIe	-	-	-	-	-	-
	DiiVA	-	-	-	-	-	-
	DisplayPort	-	-	-	-	-	-
	HDMI	-	-	-	-	-	-
	MHL	-	-	-	-	-	-
	SATA	-	-	-	-	-	-
	SAS3	-	-	-	-	-	-
	Thunderbolt	-	-	-	-	-	-
Memory	UHS-II	-	-	-	-	-	DDRA
	DDR	-	-	-	SR-ENET	SR-ENET	ET3
Datocom	Ethernet	-	-	-	-	-	MTM
	Comm. Mask Testing	-	-	-	-	-	-
	Fibre Channel	-	-	-	-	-	-
	10GBASE-T KR	-	-	-	-	-	-
	SFP+	-	-	-	SR-CUST	SR-CUST	-
Advanced Analysis	Custom Serial	-	-	-	SR-810B	SR-810B	-
	8b/10b	-	-	-	-	-	-
	NRZ Serial	-	-	-	-	-	-
	PAM4	-	-	-	-	-	-
	Serial Data Link Analysis	-	-	-	-	-	-
	Jitter & Eye Diagram Analysis	-	-	-	-	-	DJA (DJE incl. std), DJAN

Contact Information

Australia* 1 800 709 465
Austria 00800 2255 4835
Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777
Belgium* 00800 2255 4835
Brazil +55 (11) 3759 7627
Canada 1 800 833 9200
Central East Europe / Baltics +41 52 675 3777
Central Europe / Greece +41 52 675 3777
Denmark +45 80 88 1401
Finland +41 52 675 3777
France* 00800 2255 4835
Germany* 00800 2255 4835
Hong Kong 400 820 5835
India 000 800 650 1835
Indonesia 007 803 601 5249
Italy 00800 2255 4835
Japan 81 (3) 6714 3086
Luxembourg +41 52 675 3777
Malaysia 1 800 22 55835
Mexico, Central/South America and Caribbean 52 (55) 56 04 50 90
Middle East, Asia, and North Africa +41 52 675 3777
The Netherlands* 00800 2255 4835
New Zealand 0800 800 238
Norway 800 16098
People's Republic of China 400 820 5835
Philippines 1 800 1601 0077
Poland +41 52 675 3777
Portugal 80 08 12370
Republic of Korea +82 2 565 1455
Russia / CIS +7 (495) 6647564
Singapore 800 6011 473
South Africa +41 52 675 3777
Spain* 00800 2255 4835
Sweden* 00800 2255 4835
Switzerland* 00800 2255 4835
Taiwan 886 (2) 2656 6688
Thailand 1 800 011 931
United Kingdom / Ireland* 00800 2255 4835
USA 1 800 833 9200
Vietnam 12060128

* European toll-free number. If not accessible, call: +41 52 675 3777

Rev. 02.2018

Find more valuable resources at TEK.COM

Copyright © Tektronix. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks or registered trademarks of their respective companies.
081618 46W-31080-4

