

TBS2000 Series vs. Rigol DS2000A Series

COMPETITIVE FACT SHEET

Visualization

Tektronix TBS2000 Series



- ✓ 9" WVGA display with 15 horizontal grids
- ✓ 20M record length to capture long time windows

Rigol DS2000A Series



- ✗ 8" WVGA with 14 horizontal grids
- ✗ 14M record length as standard, with a 56M option

Key Specifications Comparison

| | Tektronix TBS2000 Series | | Rigol DS2000A Series | |
|--------------------------------------|--------------------------|---------------------------------|----------------------|--|
| Analog Channels | ✓ | 2, 4 | ✗ | 2 |
| Bandwidth | ✗ | 70, 100 MHz | ✓ | 70, 100, 200, 300 MHz |
| Max. Sample Rate (All channels on) | ✗ | 500 MS/s | ✓ | 1 GS/s |
| Max. Record Length (All channels on) | ✓ | 20 M points | ✗ | 7 M points 28 M points (optional) |
| Time-base Range | ✓ | 2ns/div to 100s/div (70&100MHz) | ✓ | 5ns/div to 1ks/div (70&100MHz) 2ns/div to 1ks/div (200MHz) 1ns/div to 1ks/div (300MHz) |
| Auto Measurement | ✓ | 32 | ✗ | 29 |
| Standard Trigger Types | ✗ | Edge, Pulse width, Runt | ✓ | Edge, Pulse width, Runt, Slope, Pattern, Setup/Hold, RS-232, I ² C, SPI |

Probe and Measurement

Tektronix TBS2000 Series



- ✓ TekVPI probe interface supports active, differential, and current probes without the need for external power. Probes communicate with TBS2000
- ✓ 32 automatic measurements can be categorized and laid out in one page for straight-forward selection
- ✓ Cursor measurement with on-waveform readouts

Rigol DS2000A Series



- ✗ Standard BNC interface. No power provided by the scope, and no communication
- ✗ 24 automatic measurements are selected from a long list. You are not able to see them all at once
- ✗ Cursor measurement readouts are off to the side of the screen

Safety and Reliability

Tektronix TBS2000 Series

- ✓ 5 years of warranty
- ✓ No fans in 2-channel models, for low noise operation
- ✓ Max. Input Voltage: CATII 300Vrms

Rigol DS2000A Series

- ✗ 3 years of warranty
- ✗ Fans in all models
- ✗ Max. Input Voltage: CATII 100Vrms



TBS2000 Series vs. Rigol DS2000A Series

COMPETITIVE FACT SHEET

Education for Everybody

Tektronix TBS2000 Series

- ✓ **HelpEverywhere** – Shows real-time instructions for key operations like triggering or measuring
- ✓ **ScopeIntro** – Built-in knowledge book with detailed introduction of oscilloscope and current models
- ✓ **Courseware** – Lab exercises may be downloaded for free and may be loaded and viewed on the oscilloscope
- ✓ **TekSmartLab** – TBS2000 is fully compatible with TekSmartLab software for presetting lab stations and monitoring student progress from a professor's workstation



Rigol DS2000A Series

- ✗ No instructions for key operations
- ✗ No built-in oscilloscope or operation guide
- ✗ Lab exercises may not be loaded or viewed on the oscilloscope
- ✗ No solution for presetting lab stations or monitoring student progress during labs from a professor's workstation

Remote Connectivity

Tektronix TBS2000 Series



- ✓ First basic oscilloscope with Wi-fi Dongle support
- ✓ Two USB ports on rear panel: one USB HOST for flash drive or wi-fi dongle; one USB DEVICE for remote control via PC
- ✓ LAN with LXI compatibility is included. TBS2000 can be remotely accessed on any device on the network equipped with a web browser

Rigol DS2000A Series



- ✗ No wireless connectivity
- ✗ Only one USB port on rear panel: USB DEVICE
- ✓ LAN as standard with LXI compatibility