

**TLA7016 Tektronix Logic Analyzer
Declassification and Security
Instructions**

Copyright © Tektronix. All rights reserved. Licensed software products are owned by Tektronix or its subsidiaries or suppliers, and are protected by national copyright laws and international treaty provisions.

Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specifications and price change privileges reserved.

TEKTRONIX and TEK are registered trademarks of Tektronix, Inc.

Contacting Tektronix

Tektronix, Inc.
14200 SW Karl Braun Drive
P.O. Box 500
Beaverton, OR 97077
USA

For product information, sales, service, and technical support:

- In North America, call 1-800-833-9200.
- Worldwide, visit www.tektronix.com to find contacts in your area.

Date: Aug. 14, 2006

Subject: Memory Erasure & Memory Parts in TLA7016.

MEMORY ERASURE PROCEDURE

- Turn the power off for at least 20 seconds to clear volatile memory.

MEMORY PARTS

Enhanced Monitor Board P/N: 671-6146-00

Part Number	Reference designator	Description	Use
160-9691-01	U24	IC, Memory, CMOS, EPROM, 64K X 16	EPROM: Stores the instrument code.
156-7366-00	U29 U31	IC, Memory, CMOS, DRAM, 1M X 16	DRAM: Stores the instrument code in volatile memory.
156-6869-00	U22 U25	IC, Memory, CMOS, Flash, 512K X 8	Flash: Stores the instrument code.
163-0690-00	U44	IC, Memory, CMOS, PROM, 212K X 1	PROM: Stores the FPGA image for instrument control.
156-6510-01	U1	IC, Memory, CMOS, EPROM, 1K X 8, Serial	EPROM: Stores the instrument code.

Slot 0 Controller Board P/N: 671-5924-01

Part Number	Reference designator	Description	Use
156-8978-00	U0272 U273	IC, Memory; CMOS, SDRAM; 4M X 16BIT X 4	SDRAM: Stores the instrument code in volatile memory.
156-9307-00	U382	IC, Memory; CMOS, Flash; 4M X 8	Flash: Stores the instrument code and MAC address in non-volatile memory.
156-9540-00	U471	IC, Memory; CMOS, Flash; 2M (512 X 4)	Flash: Stores the instrument model number and serial number in non-volatile memory.
156-9696-00	U0381	IC, Memory; Serial Configuration Device, 1MBit	PROM: Contains the FPGA image for instrument control in non-volatile memory.
156-9811-00	U572	IC, Memory; CMOS, PROM, 4M	PROM: Contains the FPGA image for instrument control in non-volatile memory.
156-9573-00	U641 U642	IC, Memory; CMOS, Flash; 16M X 8	Flash: Stores the instrument code and MAC address in non-volatile memory.
167-0447-00	J431	IC, Memory, DRAM; 64MX64, 512MB, DDR, 333MHZ, CL-2.5, SODIMM 200	DRAM: Stores the instrument code in volatile memory.

If you have any questions, contact the Tektronix Technical Support Center at 1-800-833-9200*3.