Version 1.0 November 2011

Introducing the Keithley IVI Driver for 2200 Series of Programmable DC Power Supplies

The Keithley2200 IVI COM driver conforms to the IVI driver standards and specifications. The help file included with the driver contains the detailed driver functionality description and programming information. This readme file contains additional information for the user. The driver uses the services provided by IVI Shared components (provided by IVI foundation) and VISA. The driver can be used with GPIB or USB.

Supported Instruments

2200-20-5, 2200-30-5, 2200-32-3, 2200-60-2, 2200-72-1

Installation

System Requirements: The driver installation will check for the following requirements. If not found, the installer will either abort, warn, or install the required component as appropriate.

Supported Operating Systems: Windows 2000 Windows XP Windows Vista Windows 7

Shared Components

Before this driver can be installed, your computer must already have the IVI Shared Components installed.

Minimal IVI Version: 2.0

The IVI Shared Components installer is available from: http://www.ivifoundation.org/shared_components/Default.aspx

VISA

The following implementations of VISA are compliant with this driver: $NI-VISA^{IM}$, $TekVISA^{IM}$, AGILENT IO Libraries Suite. The Keithley I/O Layer supplies a $NI-VISA^{IM}$ runtime. Downloads are available at www.keithley.com/support or you may follow the link below:

http://www.keithley.com/support/keidoc_searchresult?keyword=KIOL&item_type=Software + Driver)

Additional Setup

.NET Framework

The .NET Framework itself is not required by this driver. If you plan to use the driver with .NET, the minimal .NET framework version is 2.0.

The .NET Framework requires an interop assembly for a COM server. A Primary Interop Assembly, along with an XML file for IntelliSense is installed with the driver. The driver's PIA, along Page 1

Readme.txt

with IVI PIAs are installed, by default, in: <drive>:\Program Files\IVI Foundation\IVI\Bin\Primary Interop Assemblies

The PIA is also installed into the Global Assembly Cache (GAC) if you have the .NET framework installed.

Help File

The help file (Keithley2200.chm) is located in the directory: <drive>:\Program Files\IVI Foundation\IVI\Drivers\Ke2200

Examples

The driver installs few examples written in VisualBasic 6.0, C Sharp .NET, C++ and VB.NET. Examples are located in the directory:

<drive>:\Program Files\IVI Foundation\IVI\Drivers\Ke2200\Examples

Revision History

Version Date Notes

1.0.0 Oct,2011 Initial public release

IVI Compliance

IVI-COM/IVI-C Specific Instrument Driver

IVI Instrument Class: IviDCPwr

IviDCPwrBaseyesIviDCPwrMeasurementyesIviDCPwrTriggernoIviDCPwrSoftwaretriggeryes

Optional Features:

Interchangeability Checking no State Caching no Coercion Recording no

Driver Identification:

Vendor: Keithley

Description: 2200 Series Power Supply

Revision: 1.0.

Component Identifier: Keithley2200

IVI-C prefix: Ke2200

Hardware Information:

Instrument Manufacturer: Keithley

Supported Instrument Models: 2200-20-5,2200-30-5,2200-32-3,2200-60-2,2200-72-1

Supported Bus Interfaces: GPIB, USB

32-bit Software Information:

Supported Operating Systems: Windows 2000, Windows XP, Windows Vista 32, Windows 7

Support Software Required: VISA

Source Code Availability: Source code included with driver.

64-bit Software Information:

Supported Operating Systems: Windows Vista 64 , Windows 7

Support Software Required: VISA

Source Code Availability: Source code included with driver.